



Aral Getriebeöl EP SYNTH 75W-90

High-performance transmission fluid

Description

Aral Getriebeöl EP Synth. SAE 75W-90 is a high-performance transmission fluid with Aral Synthesis Technology for use in manual car transmissions and transaxles. It is also suitable for use in manual transmissions and auxiliary drives in commercial vehicles and motorcycles.

Aral Getriebeöl EP SYNTH. SAE 75W-90 is a multi-grade fluid with low-friction characteristics. It can be used when experiencing shifting trouble (stiffness, noise) instead of single-grade API GL 4 (SAE 80W, 85W-90) fluids.

Typical Characteristics

Name	Method	Units	Aral Getriebeöl EP Synth. 75W-90
Density @ 15C	DIN EN ISO 12185	g/ml	0.866
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.63
Viscosity Index	DIN ISO 2909	None	198
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	77.6
Pour Point	ISO 3016	°C	-51
Flash Point, COC	DIN-ISO 2592	°C	218
Viscosity, Brookfield @ -40C	DIN 51398	mPa.s (cP)	27000

Product Performance Claims

API GL-4+

VW 501 50

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral Getriebeöl EP SYNTH 75W-90

21 Jan 2013

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

www.aral-lubricants.de